XCMG | SOLID TO SUCCEED

ROUGH TERRAIN SCISSOR LIFT
XG2225RT

Standard configuration

Work Area
- Withdrawable Platform Extension With Position Lock
- Lanyard Attach Points
- Self-Locking Half-Height Swing Gate And Folding Guardrail

Drive
- 4-Wheel Drive
- 4-Wheel Steering

Performance
- Full Proportion Travel And Lift Control
- 30 % Gradeability

Power
- Kubota Engine(EU V)

Safe
- Emergency Stop Devices On Platform And Ground Controls
- Load Sensing Alarm System
- Descent Alarm
- 3-Second Descent Delay
- Multi-Axis Tilt Sensor
- Multi-Disc Brake
- Boom Maintenance Lock
- Auto Brake System
- Fault Diagnosis System
- Electric Horn
- Automatic High-Altitude Speed-Limit Travel Protection
- Tilt Protection System
- Outrigger Leveling System
- Emergency Descent System
- Emergency Pump

Other Features
- Removable Platform Control
- Hourmeter
- Flashing Indicator Light
- User-Friendly Control System
- Full-Height Driving

Working height
22 meters

Lift capacity
750Kg

Diesel
power



Optional configuration

- Non-Marking Tires
- Platform Searchlight
- Air Line
- Platform Fire Extinguisher
- Platform Foot Pedal

BMD KRAN-TRANS D.O.O.

Sedmog Jula 23b, 11262 Velika Moštanica, Beograd, Srbija
info@bmdkrantrans.rs


XG2225RT


XCMG SOLID TO SUCCEED

Rough Terrain Scissor Lift-Engine Powered


Item	Metric
Dimension	
Max. Working Height	22m
Max. Platform Height	20m
Min. Platform Height	2.66m
Maximum Drive Height	20m
Overall Length (Without Ladder/Outriggers)	4944mm
Overall Width	2455mm
Overall Height (Platform Folded)	3840(2995)mm
Platform Length	4590mm
Platform Width	2250mm
Platform Extension Length	2700mm
Outrigger Span (Side To Side/ Front And Rear)	2110mm/4610mm
Wheelbase	3300mm
Min. Ground Clearance	390mm
Tire Size	φ915mm×356mm
Performance	
Rated Load	750kg
Load On Platform Extension	750kg
Max. Platform Occupancy (Indoor/Outdoor)	4/4
Max. Driving Speed (Stowed)	5.0km/h
Max. Driving Speed (Raised)	0.4km/h
Max. Gradeability	30%
Min. Turning Radius (Inside)	1.6m
Min. Turning Radius (Outside)	2.5m
Platform Raising Time	90s
Platform Lowering Time	95s
Max. Working Slope (Side To Side/Front And Rear)	2°/3°
Tire Ground Pressure	4.85kg/cm²
Driving Wheels	4
Braking Wheels	4
Steering Wheels	4
Power Source	
Engine Model	Kubota v2403
Engine Power / Rpm	36.8kW/2700rpm
Max. Engine Torque	159.8N · m
Hydraulic Oil Capacity	
Hydraulic Tank Capacity	155L
Fuel Tank Capacity	100L
Weight	
Machine Weight	13700kg

Trans





Platform Extd



The print does not belong to the contract, nor a part of the commercial contract. We reserve the right to revise the product model, parameters, configuration based on the continuous improvment requirements of the product, without prior notice. Pictures are for reference only, and the specific product shall depend on the real product. The final interpretation rights belong to XCMG.