XCMG | SOLID TO SUCCEED

ARTICULATED BOOM LIFT
XGA16H

Working height 16.3meters

Lift capacity 320kg

Hybrid power



Standard configuration

Work Area

- 1.83 m× 0.76 m Work Platform

Power

- 12V DC Auxiliary Power
- Lithium Battery
- Engine And Components

Drive

- Axle Drive
- Axle Oscillation

Safe

- Descent And Motion Alarm
- Tilt Alarm
- Horn
- Overload Alarm
- Work Platform Tilt Protection
- Motor Overload Protection
- Emergency Stop Devices On Platform And Chassis
- Emergency Power Unit
- Axle-Drive Braking System

Other Features

- Automatic Leveling System
- Proportional Joystick Control
- Drive Enable
- Telematics Front-End Interface
- Anti-Entrapment System
- Platform Power
- Tool Tray

Optional configuration

- Air Line
- Mechanical Anti-Entrapment Device
- Platform Height Limitation Anti-Collision Device
- Platform Half-Mesh
- Working Light Assembly
- Fall Arrest Assembly
- Platform Anti-Squeeze Auxiliary Rail
- Aircraft Protection Device
- Rubber Buffer Protection Device

BMD KRAN-TRANS D.O.O.


Sedmog Jula 23b, 11262 Velika Moštanica, Beograd, Srbija
info@bmdkrantrans.rs

XGA16H


XCMG SOLID TO SUCCEED


Articulated Boom Lift-Hybrid

Item		Metric
Dimension		
Overall Dimension - Stowed	Length	6970mm
	Width	2300mm
	Height	2570mm
Overall Dimension - Transported	Length	6970mm
	Width	2300mm
	Height	2570mm
Platform Dimensions	Length	1830mm
	Width	760mm
	Height	1150mm
Wheelbase		2500mm
Overall Width		2300mm
Jib Length		1850mm
Min. Ground Clearance		300mm
Performance		
Max. Working Height		16.3m
Max. Platform Height		14.3m
Max. Outreach		8.8m
Max. Up And Over Clearance		7.2m
Max. Lift Capacity		320kg
Max. Platform Occupancy		2
Max. Chassis Allowable Angle		X-5°/ Y-5°
1st Boom Luffing Range		0°～72°
2nd Boom Luffing Range		-2.5°～75°
Fly Boom Luffing Range		-65°～70°
Turntable Rotation		360°
Platform Rotation		160°
Machine Weight		8200kg
Driving Speed (Stowed)		6.0 km/h
Driving Speed (Raised Or Extended)		0.6 km/h
Min. Turning Radius (Inside/Outside)		3200mm/5200mm(2) 1600mm/3500mm(4)
Turntable Tailswing		0
Max. Gradeability (Counterweight Downhill)		40%(22°)
Power source		
Control		12 V DC proportional control
Main Power Unit		12kW/31V
Auxiliary Power Unit		1.9kW/12V
Traveling Motor		9kW/34VAC
Emergency Power Supply		12V/120Ah
Main Power Source - Battery		346Ah/51.2V (Li)
Main Power Source - Charger		48V/60A
Engine Model		Kubota Z482
Engine Power / Rpm		9.8kW/（3600r/min）
Max. Engine Torque		29.7N · m（2600r/min）
Engine Emission Standard		EU Ⅴ
Hydraulic Tank Capacity（Effective Volume）		91L
Fuel Tank Capacity		95L
Tire		
Tire Size		ϕ 836mm×319mm
Ply Rating Of Tire		18
Tire Ground Pressure		6.4kg/cm²
Driving Wheels		4
Braking Wheels		4
Steering Wheels		4





Stowed





Trans





The print does not belong to the contract, nor a part of the commercial contract. We reserve the right to revise the product model, parameters, configuration based on the continuous improvment requirements of the product, without prior notice. Pictures are for reference only, and the specific product shall depend on the real product. The final interpretation rights belong to XCMG.