XCMG | SOLID TO SUCCEED

ARTICULATED BOOM LIFT
XGA18K

Standard configuration

Work Area
- Tri-Entry Platform With Side Swing Gate

Power
- Cold Start Components
- Engine Intake Air Pre-Filter Assembly
- Engine Condition Monitoring And Start Protection Device

Drive
- 4-Wheel Drive
- Axle Oscillation

Safe
- Descent And Motion Alarm
- Tilt Alarm
- Horn With Adjustable Volume
- Emergency Stop Devices On Platform And Chassis
- Emergency Power Unit
- Axle Oscillation Pressure Detection System
- 4-Wheel Braking System

Other Features
- Automatic Leveling System
- Proportional Joystick Control
- Drive Enable
- Two-Speed Drive
- Telematics Front-End Interface
- Anti-Entrapment System
- Hostile Environment Package
- Swing-Out Engine Tray
- Thumb Rocker Steering
- Platform Power
- Tool Tray

Working height
18.01 meters

Lift capacity
256/350kg

Diesel
power



Optional configuration

- Foam-Filled Tires (Φ833mm×319mm)
- Solid Tires φ835mm×290mm
- Hydraulic Generator
- Fall Arrest Assembly
- Platform Anti-Squeeze Auxiliary Rail
- Platform Half-Mesh
- Air Line
- Mechanical Anti-Entrapment Device

BMD KRAN-TRANS D.O.O.


Sedmog Jula 23b, 11262 Velika Moštanica, Beograd, Srbija
info@bmdkrantrans.rs

XGA18K


SOLID TO SUCCEED


Articulated Boom Lift-Engine Powered

Item		Metric
Dimension		
Overall Dimension - Stowed	Length	7640mm
	Width	2300mm
	Height	2380mm
Overall Dimension - Transported	Length	5700mm
	Width	2300mm
	Height	2550mm
Platform Dimensions	Length	1830mm
	Width	760mm
	Height	1150mm
Wheelbase		2360mm
Jib Length		1420mm
Min. Ground Clearance		300mm
Performance		
Max. Working Height		18.01m
Max. Platform Height		16.01m
Max. Outreach		10.26m
Max. Up And Over Clearance		7.7m
Max. Lift Capacity		256/350kg
Max. Platform Occupancy		2/3
Max. Chassis Allowable Angle		X-5°/Y-5°
1st Boom Luffing Range		0°～65°
2nd Boom Luffing Range		-11°～75°
Fly Boom Luffing Range		-60°～70°
Turntable Rotation		360°
Platform Rotation		160°
Machine Weight		9150 kg
Driving Speed (Stowed)		5.5km/h
Driving Speed (Raised or Extended)		0.6km/h
Min. Turning Radius (Inside/Outside)		3200mm/4700mm
Turntable Tailswing (Stowed)		0
Max. Gradeability (Counterweight Downhill)		45% (24°)
Power source		
Control		12 V DC proportional control
Emergency Power Supply		12V/180Ah
Engine Model		Kubota V2403-CR-EW02
Engine Power / Rpm		36.8 kW(2700 r/min)
Max. Engine Torque		157.4N · m/(1600r/min)
Engine Emission Standard		EU Ⅴ
Hydraulic Tank Capacity (Effective Volume)		80L
Fuel Tank Capacity		65 L
Tire		
Tire Size		φ833mm×319mm
Ply Rating Of Tire		18
Tire Ground Pressure		7.93 kg/cm²
Driving Wheels		4
Braking Wheels		4
Steering Wheels		2





Stowed





Trans





The print does not belong to the contract, nor a part of the commercial contract. We reserve the right to revise the product model, parameters, configuration based on the continuous improvment requirements of the product, without prior notice. Pictures are for reference only, and the specific product shall depend on the real product. The final interpretation rights belong to XCMG.